

**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

## Section 1: Identification of the substance or mixture and the company

### 1.1. Product Identifier

EM-Tec C39 strong conductive carbon cement

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Against electrostatic charge, bonding SEM samples and making grounding paths for SEM samples

### 1.3. Details of the supplier of the Safety Data Sheet

Vof Micro to Nano  
Wateringweg 79  
2031EK Haarlem  
Netherlands  
Tel: +31(0)85-2013155  
E: info@microtonano.com

### 1.4 Emergency telephone number

112 (NLD) or your national emergency telephone number for chemical spills, leaks, fires, exposures or accidents

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

<b>Physical:</b>	Flammable liquid, category 2 Highly flammable liquid and vapour
<b>Health:</b>	Aspiration irritation, category 1 Skin corrosion/irritation category 2 Eye irritation, category 2 Causes serious eye irritation Specific target organ toxicity – single exposure, category 3 May cause drowsiness or dizziness
<b>Environment:</b>	Not classified
<b>Other hazards:</b>	None

### Classification according to Regulation EC Nr. 1272/2008

F: HIGHLY FLAMMABLE



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

	Xi: Irritant Xn: Harmful
<b>Health:</b>	R36: Irritating to eyes R38: Irritating to skin R40 (3): Limited evidence of carcinogenic effect R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation R63 (3): Possible risk of harm to the unborn child R67: Vapours may cause drowsiness and dizziness
<b>Physical</b>	R11: Highly flammable R7 : May cause fire
<b>Environment:</b>	Not classified
<b>Other hazards:</b>	Not classified

## 2.2 Labeling elements

### Labelling accordance to Regulation EC Nr. 1272/2008

**Hazard pictogramm(s):**



**Signal word:**

**Danger**

**Hazard statement(s):**

H225: Highly flammable liquid and vapour  
H315: Causes skin irritation  
H319: Causes serious eye irritation  
H336: May cause drowsiness or dizziness  
H351: Suspected of causing cancer  
H361d: Suspected of damage to the unborn child  
H373: May cause damage to organs through prolonged or repeated exposure

**Precautionary statement(s)**

**Prevention:**

P102: Keep out of reach of children  
P 201: Obtain special instructions before use  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233: Keep container tightly closed  
P241: Use explosion proof electrical/ventilating/lighting/intrinsically safe equipment  
P242: Use only non-sparking tools  
P243: Take precautions against static discharge  
P260: Do not breath dust/fumes/gas/mist/vapours/spray  
P 271: Use outdoors or in well ventilated area (fume hood)  
P280: Wear protective gloves/protective clothing/eye protection/face protection



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

**Response:** P301+P310: If swallowed: Immediately call a poison Center/doctor/physician/first aider  
P308+P313: If exposed or concerned: Get medical attention  
P331: No NOT induce vomiting  
P370+P378: In case of fire: Use alcohol resistant foam or protein foam for extinction  
P305+P351+P338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if easy to do. Continue rinsing.  
P337+P313: If eye irritation persists: Get medical attention  
P302+P352: If on skin: Wash with plenty of water and soap.  
P303+P361+P353: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304+P340: If inhaled: Remove person to fresh air and keep comfortable for breathing  
P332+P313: If skin irritation occurs: Get medical attention  
P362+P364: Take of contaminated clothing and wash before resue  
**Storage:** P403+P235: Store in a well-ventilated place. Keep cool.  
P405: Store locked up  
**Disposal:** P501-2: Dispose of contents/container to an authorised waste collection point  
**Supplemental hazard info:** None

## 2.3 Other hazards

None

## Section 3: Composition / information on components

### 3.1. Substances

Not applicable

### 3.2 Mixtures

1. CAS Nr 2. EC Nr 3. Index Nr 4. REACH No	% (weight)	Name	Classification according to directive 67/548/EEC [DSD]	Classification according to regulation Nr 1272/2008 [CLP]
108-88-3 203-625-9 601-021-00-3 01-2119471310-51-xxxx	10-30	toluene	R11R38R48/20R63 R65R67	Flam.Liq. 2, Repr. 2, Asp Tox. 1 STOT RE 2, Skin Irrit.2, STOT RE 3, H225, H361d, H304, H373, H315, H336(3)
7782-42-5	10-30	graphite	R48/20	STOT-RE category 2; H373



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

231-955-3 not available 01-2119486977-12-xxxx				
110-43-0 203-767-1 606-024-00-3 01-2119902391-49-xxxx	5-10	Amyl/methyl ketone	R10R20/22	Flam. Liq. 3, Acute Tox, 4; H226, H332, H302
67-64-1 200-662-2 606-001-00-8 01-2119471330-49-xxxx	5-10	acetone	R11R36R66R67	Flam. Liq. 2, Eye Irri. 2, STOT SE 3; H225, H319, H336, EUH066
64-17-5 200-578-6 603-002-00-5 01-2119457610-43-xxxx	5-10	ethanol	R11	Flam. Liq. 2; H225
110-19-0 203-745-1 607-026-00-7 01-2119488971-22xxxx	5-10	Isobutyl acetate	R11R66	Flam. Liq. 2; H225,EUH066
108-65-6 203-603-9, 283-152-2 607-195-00-7 01-2119475791-29-xxxx	1-5	Propylene glycol monomethyl ether acetate, alpha isomer	R10	Flam. Liq. 2; H226
141-78-6 205-500-4 607-022-00-5 01-2119475103-46-xxxx	1-5	Ethyl acetate	R11R36R66R67	Flam. Liq. 2, Eye Irri. 2, STOT SE 3; H225, H319, H336, EUH066
1333-86-4 215-609-9 not available 01-2119384822-32-xxxx	0.5-1.5	Carbon black	R40(3)R7	Carcinogen Category 2; H351

(\* Explanation notes: see section 16)

## Section 4: First aid measures

### 4.1. Description of first aid measures

- Contact with eyes:** Rinse cautiously with water for several minutes. If possible, remove contact lenses. Continue rinsing.  
 Seek medical attention if irritation persists.
- Contact with skin:** Wash with water and soap.  
 Seek medical attention if irritation persists.



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

**Inhalation:** Fresh air, keep warm and at rest.  
Seek medical attention if ill effects occur

**Ingestion:** If swallowed, do not induce vomiting  
Seek immediate medical advice  
If vomiting appears imminent or occurs hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.  
Never give liquid to a person with reduced awareness  
Give water to rinse out mouth, then provide water slowly as much as casually can comfortably drink  
Avoid giving milk or oils  
Avoid giving alcohol

## 4.2. Important symptoms and effects, either immediate or delayed

**Inhalation:** Excessive inhalation of solvent vapours may give rise to nausea, blurred vision, fatigue, headaches and dizziness

**Ingestion:** May cause respiratory and digestive tract irritation  
Symptoms: sore throat, abdominal pain, nausea, vomiting

**Skin contact:** Mildly irritating to skin  
Symptoms: redness and pain

**Eye contact:** Irritating to eyes  
Symptoms: redness and pain, impaired vision

## 4.3. Indication of any immediate medical attention and special treatment

**General advise:** If you feel unwell, seek medical advice; show product label if possible  
If symptoms persist, always call a doctor

## Section 5: Firefighting Measures

### 5.1. Extinguishing media

Use dry chemical, carbon dioxide or chemical foam to extinguish

### 5.2. Special hazards arising from the substance or mixture

May form explosive vapour/air mixtures  
Forms hazardous decomposition products  
CO, CO<sub>2</sub>, nitrous oxide and smoke

### 5.3. Advice to firefighters

Keep container(s) exposed to fire cool by spraying with water  
In case of fire; do not breathe fumes  
Wear self-contained breathing apparatus for fire fighting



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources  
Ensure adequate ventilation  
Wear suitable protective clothing including eye/face protection

### 6.2 Environmental precautions

Avoid release to the environment  
Do not allow to enter public sewers and waterways

### 6.3 Methods and material for containment and clean up

Absorb spillage in suitable inert material  
Clean up spills immediately  
Avoid breathing vapours  
Control personal contact with the substance, by using protective equipment  
Collect spillage, absorbed spillage and wipes in a sealable, solvent resistant container  
Wash spill area with soap and water to remove last traces of residue

### 6.4 Reference to other sections

For further information see section 8

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

Keep away from sources of ignition  
Take precautions against static discharges  
Equipment should be grounded  
Use explosion proof electrical/ventilating/lighting/...../equipment  
Only use non-sparking tools  
Do not breathe aerosols or vapours  
Ensure adequate ventilation  
Avoid contact with skin and eyes  
Wash thoroughly after use  
Wear protective gloves/protective clothing/eye protection/face protection  
Have eyewash bottles available



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly close, in a cool, well ventilated place  
 Keep cool  
 Keep out of reach of children

## 7.3 Specific end uses(s)

Against electro-static charge  
 Making grounding paths.  
 Bonding SEM specimens

## Section 8: Exposure control and personal protection

### 8.1. Control parameters

#### Exposure limits

#### Occupational exposure limits (OEL)

Ingredient	Material Name	Source	TWA	STEL	Peak	Notes
toluene	Toulene	UK	191mg/m <sup>3</sup>	384mg/m <sup>3</sup>	Not available	Skin
		EU	191mg/m <sup>3</sup>	384mg/m <sup>3</sup>	Not available	Skin
Amyl methyl ketone	Heptan-2-one	UK	237mg/m <sup>3</sup>	475mg/m <sup>3</sup>	Not available	Skin
		EU	238mg/m <sup>3</sup>	475mg/m <sup>3</sup>	Not available	Skin
acetone	Acetone	UK	1210mg/m <sup>3</sup>	3620mg/m <sup>3</sup>	Not available	Not available
		EU	1210mg/m <sup>3</sup>	Not available	Not available	Not available
ethanol	Ethanol	UK	1920mg/m <sup>3</sup>	Not available	Not available	Not available
Isobutyl acetate	Isobutyl acetate	UK	724mg/m <sup>3</sup>	903mg/m <sup>3</sup>	Not available	Not available
Propylene glycol monomethyl ether acetate	1-Methoxypropyl acetate	UK	274mg/m <sup>3</sup>	548mg/m <sup>3</sup>	Not available	Skin
		EU	275mg/m <sup>3</sup>	548mg/m <sup>3</sup>	Not available	Skin
ethyl acetate	Ethyl acetate	UK	200ppm	400ppm	Not available	Not available
carbon black	Carbon black	UK	3.5mg/m <sup>3</sup>	7mg.m <sup>3</sup>	Not available	Not available

### 8.2 Exposure controls

**Control procedures:** Ensure adequate ventilation  
 Keep away from heat sources and ignition sources  
 Take precautions against static discharges



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

**Personal protection:** Take precautions to avoid contact with eyes and skin when handling the products  
Ensure adequate ventilation

**Inhalation:** In case of insufficient ventilation, wear suitable respiratory equipment:  
Air purifying respirator with organic gas/vapour cartridge (type A)

**Hands and skin:** Wear suitable gloves against chemicals; recommended gloves:  
Nitrile

**Eyes:** Wear safety goggles or full face protection

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Appearance/physical state:** Liquid  
**Colour:** Dark grey  
**Odour:** Solvent  
**pH** not applicable  
**Boiling point/range:** 56°C  
**Flash point:** -18°C (closed cup)  
**Evaporation rate:** Not available  
**Explosion limits: upper limit:** 10%  
**lower limit:** 1%  
**Vapour pressure:** Not available  
**Relative density:** 0.996 g/cm<sup>3</sup> @ 20°C  
**Solubility in water:** not soluble in water  
**Auto-ignition:** >315°C  
**Viscosity:** t>34 cSt

### 9.2 Other information

**VOC:** Not available

## Section 10: Stability and reactivity

### 10.1. Reactivity

No hazardous reactions known if used for its intended purposes

### 10.2 Chemical stability

Stable at normal temperatures and pressures



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

## 10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purposes

## 10.4 Conditions to avoid

Avoid overheating, ignition sources and incompatible substances

## 10.5 Incompatible materials

Strong oxidising agents, strong acids, strong bases

## 10.6 Hazardous decomposition products

CO, CO<sub>2</sub>, nitrous oxides and smoke

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure:

- Inhalation:** Inhalation of solvent vapours may give rise to nausea, headaches and dizziness  
**Skin contact:** Prolonged skin contact will result in defatting of the skin, leading to irritation and in some cases to dermatitis  
**Eye contact:** Irritation to eyes

#### Toxicological data:

Ingredient	Toxicity	Irritation
Toluene	Dermal (rabbit) LD: 12124mg/l	Eye (rabbit): 2mg/24h - severe
	Inhalation (rat) LC50: 49mg/l	Eye (rabbit): 100mg/30s - mild
	Oral (rat) LD50: 636 mg/kg	Skin (rabbit): 20mg/24h - moderate
Graphite, natural	Inhalation (rat) LC50: >2mg/l 4h	Eye (rabbit): non-irritating
	Oral (rat) LD50: >2000 mg/kg	Skin (rabbit): non-irritating
Amyl methyl ketone	Dermal (rabbit) LD: 12600mg/l	Skin (rabbit): 14mg/24h - mild
	Inhalation (rat) LC50: 4000ppm/4h	
	Oral (rat) LD50: 1670 mg/kg	
Acetone	Dermal (rabbit) LD: 20000mg/l	Eye (human): 500ppm - irritant
	Inhalation (rat) LC50: 50.1mg/l/8h	Eye (rabbit): 20mg/24h - moderate



# Safety Data Sheet

Regulation EC Nr. 1907/2006 Art.31

**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

	Oral (rat) LD50: 5800 mg/kg	Skin (rabbit): 500mg/24hr - mild
ethanol	Dermal (rabbit) LD: 17100mg/l	Eye (rabbit): 500mg - severe
	Inhalation (rat) LC50: 64000ppm/4h	Eye (rabbit): 100mg/24h - moderate
	Oral (rat) LD50: 11872769 mg/kg	Skin (rabbit): 20mg/24hr - moderate
Isobutyl acetate	Dermal (rabbit) LD: >5000mg/kg	moderate
	Oral (rat) LD50: 134000 mg/kg	Skin (rabbit): 500mg open mild
Propylene glycol monomethyl ether acetate, alpha isomer	Dermal (rabbit) LD: >5000mg/kg	Nil reported
	Inhalation (rat) LC50: 4345ppm/6h	
	Oral (rat) LD50: >8532 mg/kg	
Ethyl acetate	Dermal (rabbit) LD: >18000mg/kg	Eye (human):400ppm
	Inhalation (rat) LC50: >6000ppm/6h	
	Oral (rat) LD50: >10170 mg/kg	
Carbon black	Dermal (rabbit) LD: >3000mg/kg	Not available
	Oral (rat) LD50: >8000 mg/kg	
EM-Tec C39 conductive carbon cement	Not available	Not available

## Section 12: Ecological information

### 12.1. Toxicity

Not classified

### Ecotoxicological data:

Hazardous ingredient	CAS-nr	Method	
Propan-2-ol; isopropyl alcohol, isopropanol	67-63-0	IC50 algae	>1000 mg/l
		LC50 fish	>1000 mg/l
		EC50 daphnia	>1000 mg/l

### 12.2 Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)
amyl methyl ketone	LOW	LOW
acetone	LOW (Half-life = 14 days)	Medium (Half-life = 116.25 days)



**Micro to Nano**  
Innovative Microscopy Supplies

Wateringweg 79  
2031EK Haarlem  
The Netherlands

T +31-85-2013155  
E [info@microtonano.com](mailto:info@microtonano.com)  
I [www.microtonano.com](http://www.microtonano.com)

**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
Isobutyl acetate	LOW	LOW
Propylene glycol monomethyl ether acetate, alpha-isomer	LOW	LOW
Ethyl acetate	LOW (Half-life = 14 days)	LOW (Half-life = 14.71 days)

## 12.3 Bioaccumulative potential

Ingredient	Bioaccumulation
toluene	LOW (BCF = 90)
amyl methyl ketone	LOW (logKOW = 1.98)
acetone	LOW (BCF = 90)
ethanol	LOW (logKOW = 0.31)
Isobutyl acetate	LOW (logKOW = 1.78)
Propylene glycol monomethyl ether acetate, alpha-isomer	LOW (logKOW = 0.56)
Ethyl acetate	High (BCF = 90)

## 12.4 Mobility in soil

Ingredient	Bioaccumulation
toluene	LOW (KOC = 268)
amyl methyl ketone	LOW (KOC = 24)
acetone	HIGH(KOC = 1.981)
ethanol	HIGH (KOC = 1)
Isobutyl acetate	LOW (KOC = 17.48)
Propylene glycol monomethyl ether acetate, alpha-isomer	HIGH (KOC = 1.838)
Ethyl acetate	LOW (KOC = 6.131)

## 12.5 Results of PBT and vPvB assessment

No information available

## 12.6 Hazardous decomposition products

No experimental data available



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Product:** This material and its container must be disposed of in a safe way.  
Containers may still present a chemical hazard when empty  
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

**National regulations:** Disposal should be in accordance with local, state or national legislation.

## Section 14: Transport information

Label required:



### 14.1. UN number

**UN-number:** 1263

### 14.2 UN proper shipping name

**Proper shipping name:** PAINT

### 14.3 Transport hazard class(es)

**Class:** 3  
**ADR/RID-Classification code:** F1

### 14.4 Packing group

**Packing:** II  
**Limited Quantity:** 5L

### 14.5 Incompatible materials

**ADR/RID- Environmentally hazardous:** No  
**IMDG-Marine pollutant:** No  
**IATA/ICAO-Environmentally hazardous:**No



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

## 14.6 Special precautions for user

<b>ADR/RID-Tunnelcode:</b>	(D/E)
<b>IMDG-Ems:</b>	F-E, S-D
<b>IATA/ICAO-PAX:</b>	353
<b>IATA/ICAO-CAO:</b>	364

## 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Not applicable

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UN-number: 1263

### 15.2 Chemical safety assessment

No information available

## Section 16: Other information

### RoHS Directive Compliant

This product is fully compliant with the directive 2100/65/EU Annex II (RoHS). It does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's or PBDE's.

### WEEE

This product is not a piece of electrical or electronic equipment, and it therefore not governed by Directive 2002/96/EC on waste electrical and electronic equipment (WEEE)

### Abbreviations:

Asp. Tox	Aspiration hazard
Carc.	Carcinogenicity
Exp.	Exposure
Flam.	Flammable
GHS	Global Harmonised System of Classification of Labelling Chemicals
Irrit.	Irritant
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
N/A	Not applicable



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

N/E	Not estimated
PBT	Persistent Bioaccumulative and Toxic
WEL	Workplace Exposure Limit
Repr.	Reproductive toxicant
RoHS	Restriction of Hazardous Substance
SEM	Scanning Electron Microscope
STEL	Short-Term Exposure Limit
STOT	Specific Target Organ Toxicity
TCLo	Lowest published toxic concentration
vPvB	very Persistent and very Bioaccumulative
WEEE	Waste Electrical and Electronic Equipment

## DSD / DPD label elements



## Full Text Risk and Hazard codes

H220 – Extremely flammable gas.  
H226 – Flammable liquid and vapour.  
H228 – Flammable solid.  
H251 – Self-heating, may catch fire.  
H301 – Toxic if swallowed.  
H302 – Harmful if swallowed.  
H311 – Toxic in contact with skin.  
H318 – Causes serious eye damage.  
H331 – Toxic if inhaled.  
H332 – Harmful if inhaled.  
H335 – May cause respiratory irritation.  
H340 – May cause genetic defects.  
H350 – May cause cancer.  
H360 – May damage fertility or the unborn child.  
H361 – Suspected of damaging fertility or the unborn child.  
H362 – May cause harm to breast-fed children.  
H370 – Causes damages to organs.  
H371 – May cause damage to organs.  
H372 – Causes damage to organs through prolonged or repeated exposure.  
H400 – Very toxic to aquatic life.  
H410 – Very toxic to aquatic life with long lasting effects.  
H411 – Toxic to aquatic life with long lasting effects.  
H412 – Harmful to aquatic life with long lasting effects.

R10 – Flammable.  
R20/22 – Harmful by inhalation and if swallowed.  
R36 – Irritating to eyes.  
R63 – Possible risk of harm to the unborn child.



**Product name:** EM-Tec C39 conductive carbon cement  
**Document Nr.:** SDS0015001139-01

**Date:** August 14th 2015  
**Version:** 1.0

---

R66 – Repeated exposure may cause skin dryness and cracking.

**Safety advice:**

- S02 – Keep out of reach of children.
- S09 – Keep container in a well ventilated place.
- S13 – Keep away from food, drink and animal feeding stuff.
- S16 – Keep away from sources of ignition. No smoking.
- S23 – Do not breath gas/fumes/vapour/spray.
- S281 – After contact with skin, wash immediately with detergent and plenty of waterways.
- S29 – Do not empty in drains.
- S33 – Take precautionary measures against static discharges.
- S35 – This materials and its container must be disposed of in a safe way.
- S36 – Wear suitable protective clothing.
- S37 – Wear suitable gloves.
- S38 – In case of insufficient ventilation, wear suitable respiratory equipment.
- S39 – Wear eye / face protection
- S40 – In case of insufficient ventilation, wear suitable respiratory equipment.
- S41 – In case of fire and/or explosion; DO NOT breathe fumes.
- S45 – In case of accident or if you feel unwell, immediately contact Doctor or Poisons information center (show label if possible).
- S46 – If swallowed, seek immediate medical advice and show label if possible.
- S52 – Not recommended for interior use on large surfaces.
- S56 – Dispose of this materials and its container at hazardous or special waste collection point.
- S64 – If swallowed, rinse mouth with water (only if person is conscious)

This product should be stored, handled and used in accordance with good industrial hygiene practices and in accordance with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe the product from the point of view of safety requirements. It does not guarantee any specific properties.

It is the responsibility of the user to query and verify any information seeming suspect or where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, state, federal and international regulations.

